


MD120 Connector, Plug



MD

DIMENSIONS/POSITIONS

MD120-500

| | | |
|--------|-------------------------|-----------------------------|
| 間距 | Pitch | 5.00mm |
| 位數 | Poles | 2 ~ 20Poles |
| 塑膠本體 | Housing Material | PA 66 |
| 壓線圈 | Cage Clamp | Brass, Tin Plated |
| 夾片 | Contact | Phosphor Bronze, Tin Plated |
| 螺紋 | Screw Thread | M2.6, Steel, Zinc Plated |
| 電線線徑 | Wire Size | 14 ~ 22AWG |
| 最大緊固扭矩 | Tightening Torque, Max. | 2.75 Lb-in |
| 環境作業溫度 | Operating Temperature | -40°C to +105°C |

TECHNICAL DATA

| | | |
|---|--------------------------------|--------------------|
| 連接符合標準 Connection in acc. with standard EN-VDE | | |
| 額定電流 I _n | Nominal Current I _n | 12A |
| 額定橫截面 | Nominal Cross Section | 1.5mm ² |
| 最大負載電流 | Maximum load current | 12A |
| 絕緣材料 | Insulating Material | PA |
| 阻燃等級,符合UL94 Inflammability class acc. to UL94 | | V0 |
| 額定電壓,UL/CUL Nominal voltage, UL/CUL | | 300V |
| 額定電流,UL/CUL Nominal current, UL/CUL | | 12A |

